


<h1>LP Gas Alarm Specifications</h1>	
Product name	LP gas alarm with external output
Type	KTS-P531、KTS-P531(S)
Detailed type	KTS-P531C、KTS-P531C(S)
Target use	LP gas only (Not intended to prevent poisoning due to incomplete combustion or lack of oxygen)
Alarm spec	More than 1/100 and less than 1/4 of the lower explosive limit concentration (LEL)
Detection method	Contact combustion type
Alarm system	Delayed-warning type auto-return red
Indicator lamp	Lamp: Immediate flashing
Warning sound	Voice synthesized sound: delay time approx. 15 seconds "false alarm prevention type" Beep-beep-beep, is there a gas leak?
Response Time	Within 30 seconds
Alarm volume	70dB/m or more
External output	Photo-coupler open collector (PC) output: Delay time approx. 1 min.
PC output For meter connection	<ul style="list-style-type: none"> • When monitoring OFF • When alarmed ①ON/OFF (every 5 seconds) [when connected to the alarm terminal of S-type meter]. ②ON [when connected to other than ①(alarm terminal of S-type meter)]. ※ S-type meter compatible function: Output method is selected according to the connection destination (① or ②) (Automatic detection of when an S-type meter is connected to the alarm terminal and when it is not)
Power indicator	Red light
Power	AC100V±10%, 50/60Hz common
Power consumption	Monitoring: approx. 1.0W, Alarm: approx. 1.4W
Operating temp.	-10 to +40° C (no condensation)
Initial Tweet Prevention	Approx. 40 seconds (red lamp blinks)
Simple inspection function	※ This function is only available for approximately 3 minutes after the initial ringing prevention time. (1) Detects gas for 10 seconds (LED starts blinking when gas is detected) (2) Alarm action Alarm (sound): 3 times, LED flashing and alarm output: 1 minute continuous (3) (3) Automatic return (after operation (2)) Automatic restart to monitored state
Power cord	KTS-P531 : Approx. 2.5 m (plug with spare outlet) KTS-P531(S) : Approx. 35 cm
Dimensions and weight	120(H) × 70(W) × 30(D)mm (excluding protrusions), approx. 280g
Installation	Wall-mounted with mounting brackets Mounting position: either portrait or landscape ※KTK-14 (sold separately) is required for installation in a switch box
Accessories	User's Manual and Warranty 1部 Inspection gas 1 In case of alarm 1
Optional goods	mounting bracket 1 cord stopper 3 Wood screw (long) 3 Wood screw (short) 2



KTS-P531C : Cord length approx. 2.5 m (plug with spare outlet)
 KTS-P531C(S) : Cord length approx. 35 cm (short cord specification)

3					MATERIAL	REMARK
2					PROJECTION	Representative model: KTS-P531
1					SCALE	NAME
MARK	COUNT	DATE	REVISION		1:1	OUTLINE VIEW AND SPECIFICATION
APPROVED	CHECKED	DRAWN	DATE	Azbil Kimmon Co.,Ltd. JAPAN		DRAWING No.
Motoyama	Ito	Komatsu	2014. 9. 1			G-KTSP531C-A000A