

<b>LP Gas Alarm Specifications</b>	
Product name	LP gas alarm
Type	K T S - P 1 0 5 D
Target use	LP gas only (Not intended to prevent poisoning due to incomplete combustion or lack of oxygen)
Alarm spec	Less than 1/4 of the lower explosive limit concentration (LEL)
Detection method	Contact combustion type
Alarm system	Immediate alarm type automatic return type
Indicator lamp	Red lamp: Immediate flashing
Warning sound	Electronic buzzer intermittent sound: Immediate
Response Time	70dB/m or more
External output	(None)
Power indicator	Red light
Holding circuit	<p>Ringing stop timing notification circuit</p> <p>Failure Detection Circuit</p> <p>Replacement Timing Notification Circuit</p> <p>High-brightness light-emitting circuit for alarm</p>
Power	AC100V±10%, 50/60Hz common
Power consumption	Monitoring: approx. 0.8W Alarm: approx. 0.9W
Operating temp.	-10 to +40° C (no condensation)
Power cord	Plug on back side of main unit
Dimensions and weight	62(H) × 78(W) × 35(D)mm* approx. 115g (excluding plug)
Installation	Plugs into an outlet for installation
Accessories	<p>User's Manual and Warranty 1、 Inspection gas 1、</p> <p>In case of alarm manual 1</p>