

<b>LP Gas Alarm Specifications</b>	
Product name	LP gas alarm
Type	KTS-P105
Target use	LP gas only (Not intended to prevent poisoning due to incomplete combustion or lack of oxygen)
Alarm spec	Less than 1/4 of the lower explosive limit concentration (LEL)
Detection method	Contact combustion type
Alarm system	Immediate alarm type automatic return type
Indicator lamp	Red lamp: Immediate flashing
Warning sound	Electronic buzzer intermittent sound: Immediate
Response Time	70dB/m or more
External output	(None)
Power indicator	Red light
Holding circuit	<p>Ringing stop timing notification circuit</p> <p>Notification circuit</p> <p>Failure Detection Circuit</p> <p>Replacement Timing Notification Circuit</p> <p>High-brightness light-emitting circuit for alarm</p>
Power	AC100V±10%, 50/60Hz common
Power consumption	Monitoring: approx. 0.8W Alarm: approx. 0.9W
Operating temp.	-10 to +40° C (no condensation)
Power cord	<p>Approx. 2.5 m (with spare outlet plug)</p> <p>Auxiliary outlet rating: AC100V 14.9A or less</p>
Dimensions and weight	78(H) × 62(W) × 31(D)mm Approx. 195g
Installation	<p>Mounting plate (sold separately)</p> <p>Mounting plate is fixed with double-sided adhesive tape or wood screws</p>
Accessories	<p>User's Manual and Warranty 1、 Inspection gas 1</p> <p>In case of alert manual 1、 cord stopper 1、</p> <p>3.1mm wood screw (for cord swing stop) 1</p>