

# Gas Flow Monitor

Type CMG□□□□



Model	For air	For city gas		For propane	For butane
Model number	CMG□□□□A	CMG□□□□G		CMG□□□□P	CMG□□□□B
Compatible gas type	Air	City gas 13A		Propane	Butane
Flow rate range: m <sup>3</sup> /h (normal)	4/10/30/80/150	4/10/30/80/150	80/150	2/4/10/25/50	1/3/8/20/40
精度	±4%RD			±6%RD	
Measuring range (rangeability)	10:1				
Minimum sensitivity flow rate	1/30 of range				
Operating pressure range	0~100kPa	0~100kPa	0~990kPa	0~100kPa	0~100kPa
Operating temperature range	-10~+60°C				
Output	1-5V/4-20mA Select by model number				
Power source	DC24V/AC100V/AC200V Select by model number				
Caliber Nominal diameter	15A/25A/40A/50A		40A/50A	15A/25A/40A/50A	
Connection standard	Rc screw		JIS10k RF	Rc screw	
Straight pipe length	15A,25A				
Material	1/4B, 1B: Aluminum die-casting (ADC12) 1 1/2B, 2B: Aluminum alloy casting (AC4A)		SCS13	1/4B, 1B: Aluminum die-casting (ADC12) 1 1/2B, 2B: Aluminum alloy casting (AC4A)	
Protective structure	IP54 (JIS C 0920) dustproof and drip-proof construction				
Weight	0.85~2kg		9~10kg	0.85~2kg	