

Name	The Specification of Battery Operated Electromagnetic Flow Meter			
Model	MGB12A200	No.	MGB12A200-E0C	1/2
		Creating	10.7.2022	

○Specification&Performance

Performance item		Diameter (mm)	MGB12A 200	
Measurement Principle		Electromagnetic detection		
Indicator	Type	LCD with back light		
	Indication	Instantaneous Flowrate / Pilot / Integrated value/Alarms		
	Alarm Function	Leakage / Excess Flow / Low Battery Voltage Reverse Flow / Empty		
	Min. Scale	1 0 L		
	Max. Total Flow	9,999,999.99		
	Instantaneous Flow Rate	9999		
	LCD with back light	By opening the cover (for 30 sec),maximum 60sec/day		
	Direction of the display	By rotating the cover, 180 °		
Performance	Q 3/Q 1 :Flow rate range	200		
	Q 1 :Minimum Flow Rate (m3/h)	3.15		
	Q 2 :Transitional Flow Rate (m3/h)	5.04		
	Q 3 :Permanent Flow Rate (m3/h)	630		
	Q4:Overload Flow Rate (m3/h)	787.5		
	Measurement starting flow rate (m3/h)	1.575		
	Permissible Error	± 5 %	$Q_1 \leq Q < Q_2$	
		± 2 %	$Q_2 \leq Q \leq Q_4$	
Q 3 Pressure loss※	$\leq 0.063 \text{ MP a}$			
Operating Condition	Working Pressure Range	0.03 ~ 1 MP a		
	Fluid Temperature※	0.1~30℃		
	Fluid Electroconductivity	50 ~ 1000 $\mu \text{ S / c m}$		
	Ambient Temperature※	5 ~ 55 ℃		
	Ambient Humidity※	0~100%RH at 40℃ Ambient Temperature		
Installation	Position	Horizontal / Vertical		
	Connection	Wafer Flanged		
Case structure	IP68 (JIS C0920)			
Standard paint color	Unpainted			

Name	The Specification of Battery Operated Electromagnetic Flow Meter			
Model	MGB12A200	No.	MGB12A200-E0C	2/2
		Creating	10.7.2022	

○Specification&Performance

Performance item		Diameter (mm)	MGB12A 200
Power supply and Battery life		Internal Lithium Battery/ Battery life 9 years	
Outline Dimension	Length(mm)	300	
	Height(mm)	426	
	Width(mm)	265	
	Height from center(mm)	293	
Weight(kg)		24.3	
Japanese Type approval number		L1123	

※The above specifications are mentioned within JIS B 8570-2.

Azbil Kimmon Co.,Ltd.