

Name	Product Specifications	Model	GKDA025-E0C	1/1
		Date	May 21, 2012	

Model	<b>GKDA type 25mm dry-type water meter (Eco-meter)</b>
-------	--

○ Specifications and Performance

Type and caliber		GKDA25 (Eco meter)		
Item				
Measuring principle	Tangential flow impeller type Double jet type			
Transmission format	Pulse unit	1 m <sup>3</sup> /P		
	Transmitter	GD2A		
Transmission wire		2-core VCTF (0.5mm <sup>2</sup> ) 1.5m		
Display	Format	Dry digital display		
	Min. scale	1 L		
	Maximum indication	9,999.9 m <sup>3</sup>		
Performance	Q3/Q1 : Measurement range	100		
	Q1 : Fixed min. flow rate	0.063 m <sup>3</sup> /h		
	Q2 : Transfer flow rate	0.1008 m <sup>3</sup> /h		
	Q3 : Maximum flow rate	6.3 m <sup>3</sup> /h		
	Q4 : Limit flow rate	7.875 m <sup>3</sup> /h		
	Tolerance	± 5%	0.063 ≤ Q < 0.1008 m <sup>3</sup> /h	
		± 2%	0.1008 ≤ Q ≤ 7.875 m <sup>3</sup> /h	
Q3 Pressure loss	Less than 0.063 MPa			
Conditions of use	Appropriate operating flow range	※ 0.23 ~ 2.5 m <sup>3</sup> /h		
	Max. allowable working pressure	1 MPa		
	Ambient operating temperature	55° C or less (according to JIS standard) Please make sure that the installation conditions are such that the ambient temp is below this level.		
	Fluid temperature range	Min. allowable operating temp. 0.1° C (according to JIS standard) Max. allowable operating temp. 30° C (according to JIS standard)		
	Mounting position	Horizontal		
External dimensions	Overall Length	210 mm		
	Overall height	112 mm		
	WIDTH	98 mm		
	Center height	35 mm		
Mounting screw	Kimmon screw	39.0 Pitch 14		
Case Material		CAC804 (unpainted)		
Weight		1.9 kg		
Type Approval Number		No. L0815		

※ How to Select a Water Meter - A Commentary for Practitioners (March 2010, Japan Water Works Association)