

適正使用流量範囲

| | | 口径 | 型式 | 適正使用流量範囲 (m ³ /h) | 月間最大使用量 (m ³) |
|---|---------|-----|---|---|---------------------------|
|  | 接線流羽根車式 | 13 | KKDA(L) NKDA(L) GKDA(L) EKDA(L) PKDA(L) | 0.1~1.0 | 100 |
| | | 20 | | 0.2~1.6 | 170 |
| | | 25 | | 0.23~2.5 | 260 |
| | | 30 | | 0.4~4.0 | 420 |
| | | 40 | | 0.5~4.0 | 420 |
|  | 軸流羽根車式 | 40 | NKDS GKDS EKDS | 0.4~6.5 | 700 |
| | | 50 | | 0.4~6.5 | 700 |
| | | 50 | | NFDW(T) GFDW(T) EFDW(T) NKDW EKDW | 1.25~17.0 |
| | | 65 | 2.0~24.0 | | 3,300 |
| | | 75 | 2.5~27.5 | | 4,100 |
| | | 100 | 4.0~44.0 | | 6,600 |
|  | 電池電磁式 | 50 | MGB12A | 0.315~63 | 45,360 |
| | | 65 | | 0.5~100 | 72,000 |
| | | 75 | | 0.5~100 | 72,000 |
| | | 100 | | 0.8~160 | 115,200 |
| | | 125 | | 1.25~250 | 180,000 |
| | | 150 | | 2~400 | 288,000 |
| | | 200 | | 3.15~630 | 453,600 |

適正使用流量範囲 m³/h

